

selecting control information in said inputted first portion of said selected one message;

selecting and outputting under the control of said control processor, other portions of said message stream to said plurality of processors., based on said control information;

processing said selected other portions of said message stream simultaneously at said plurality of processors;

controlling the timing of communicating television programming in accordance with said message stream; and

storing information evidencing the availability, use or usage of said television programming or said message stream.

3. (Unchanged) A method of processing signals at a receiver station, said receiver station having a plurality of processors, said plurality of processors including a first control processor which controls a remainder of said plurality of processors based on a message stream, said method comprising the steps of:

receiving an information transmission containing a message stream at a transmission station;

generating a control portion' of said message stream at said transmission station that is effective at a receiver station to cause said first control processor to select portions of said message stream that control said control processor and said remainder of said plurality of processors to perform different functions comprising (i) processing television programming and (ii) controlling the timing of communicating said television programming; and

transmitting said message stream to be received at said receiver station.

4. (Unchanged) A method of processing signals in a network, comprising the steps of receiving an information transmission to be transmitted; receiving an instruct signal which is effective to one of:

(a) effect a transmitter station to generate at least a first message that is effective to enable a receiver station to control the reception or presentation of television programming and meter or monitor the availability, use or usage of said television programming or said at least a first message; and

(b) effect a first receiver station to generate at least a first message that is effective to enable a second receiver station to control the

reception or presentation of television programming and meter or monitor the availability, use or usage of said television programming or said at least a first message;

receiving a transmitter control signal which operates at one of said transmitter station and said first receiver station to communicate said at least a first message to a transmitter; and

transmitting said information transmission, said instruct signal and said transmitter control signal.

5. (Unchanged) The method of claim 2, further comprising the step of programming said control processor to execute a controlled function in response to said one message.

6. (Unchanged) The method of claim 5, further comprising the step of programming said control processor to compare information stored in at least a first of said at least one register memory with control function invoking information.

7. (Unchanged) The method of claim 6, further comprising the step of programming said control processor to compare information stored in at least a second of said at least one register memory with information that identifies a length or format of at least a portion of said one message.

8. (Unchanged) The method of claim 2, wherein said at least one register memory includes an input signal register memory and said step of selecting control information in said inputted first portion of said selected one message and communicating said selected control information to a plurality of registers memories comprises:

communicating said at least a first portion of said selected one message to said input signal memory;

selecting information at said input signal memory to compare or communicate;
and

communicating said control information to at least a second of said at least one register memory.

9. (Unchanged) The method of claim 8, further comprising the step of communicating at least one of said other portions of said message stream to said input signal register memory.

10. (Unchanged) The method of claim 2, further comprising the step of controlling a switch to output at least one of said selected other portions of said message stream to a specific one of said plurality of processors.

11. (Unchanged) The method of claim 10, further comprising the step of controlling said switch to communicate said at least one of said selected other portions of said message stream from one of (1) said control processor and (2) a buffer that inputs to said control processor.

12. (Unchanged) The method of claim 10, wherein said switch outputs said at least one of said selected other portions to said control processor.

13. (Unchanged) The method of claim 10, wherein said switch outputs said at least one of said selected other portions to one of a signal processor and a central processor.

14. (Unchanged) The method of claim 10, further comprising the step of programming said control processor to control said switch based on information contained in said message stream.

15. (Unchanged) The method of claim 14, further comprising the steps of:
programming said control processor with comparison information to serve as a basis for determining the length or format of said at least one segment of said message stream; and

programming said control processor to compare information stored at said at least one register memory to said comparison information.

16. (Unchanged) The method of claim 14, wherein said control processor and said switch are located on a single microchip.

17. (Unchanged) The method of claim 2, wherein said control processor receives said at least a first portion of said message from a first of said plurality of processors and controls outputting to a second of said plurality of processors.

18. (Unchanged) The method of claim 17, wherein said first processor performs one of (1) converting information detected in said message stream based on protocols and (2) assembling processor code based on information detected in said message stream, said message further comprising the step of communicating machine language code to said second processor in said selected other portions of said message stream.

19. (Unchanged) The method of claim 2, wherein a decryptor decrypts at least some of said message stream, said method further comprising the step of outputting one or more of said selected other portions of said message stream to said decryptor.

20. (Unchanged) The method of claim 19, further comprising the steps of:
selecting at least a portion of said message stream; and
controlling said decryptor in accordance with said selected at least a portion of said message stream.

21. (Unchanged) The method of claim 20, wherein said selected at least a portion of said message stream comprises a decryption key.

22. (Unchanged) The method of claim 21, further comprising the step of decrypting at least some of said digital television signal in accordance with said decryption key.

23. (Unchanged) The method of claim 19, further comprising the steps of:
storing a decrypted portion of said at least some of said message at some or all of
said at least one register memory; and
processing decrypted portions of said message stream simultaneously.

24. (Unchanged) The method of claim 23, further comprising the step of
decrypting processor code contained in said message stream.

25. (Unchanged) The method of claim 2, wherein a standard informs said
receiver station of a signal to be processed, said method further comprising the step of
evaluating at least some of said selected one message based on said standard.

26. (Unchanged) The method of claim 25, wherein further comprising the
step of:
storing at least a portion of said standard at one or more of a Standard Word and a
Standard Length memory; and
programming said receiver station to compare data received in said information
transmission to information contained at said one or more of a Standard Word and a
Standard Length memory.

27. (Unchanged) The method of claim 25, wherein said receiver identifies,
based on said standard, one of (1) an end of a prior message and (2) a header in said
selected one message.

28. (Unchanged) The method of claim 25, further comprising the step of causing said control processor to process an interrupt signal based on said standard.

29. (Unchanged) The method of claim 2, further comprising the step of programming said receiver station to communicate a processor interrupt signal to at least one of said plurality of processors.

30. (Unchanged) The method of claim 29, wherein two or more of said plurality of processors are adapted to communicate or respond to processor interrupt signals, said method further comprising the step of programming said receiver station to select at least one of said two or more processors to interrupt.

31. (Unchanged) The method of claim 30, wherein said control processor selects said at least one of said two or more processors, said method further comprising the steps of:

detecting a processor interrupt signal in said information transmission; and
inputting said processor interrupt signal to said control processor.

32. (Unchanged) The method of claim 2, wherein said receiver station includes a video monitor and a first of said plurality of processors generates a video signal to be displayed as part of said television programming, said method further comprising the step of outputting to said first processor a first of said selected other portions of said message stream which causes said first processor to communicate said video signal to said video monitor.

33. (Unchanged) The method of claim 32, wherein said receiver station includes a speaker and a second of said plurality of processors generates an audio signal containing audio to be emitted as part of said television programming, said method further comprising the step of outputting to said second processor a second of said selected other portions of said message stream which causes which causes said second processor to communicate said audio signal to said speaker.

34. (Unchanged) The method of claim 33, wherein said receiver station includes one or more of a tuner and a portion receiver and a third of said plurality of processors is adapted to control said one or more of a tuner and a portion receiver, said method further comprising the step of programming said third processor to control said one or more of a tuner and a portion receiver based on information contained in said selected other portions of said message stream.

35. (Unchanged) The method of claim 2, wherein at least one of said selected other portions of said message stream contains first processor code that controls at least one of said plurality of processors to generate information content of one or more video or audio signals, said method further comprising the steps of:

selecting second processor code contained in said selected one message; and
communicating said first processor code in accordance with said second processor code.

36. (Unchanged) The method of claim 35, wherein said second processor code programs said control processor to select control information in said message stream and communicate said selected control information to said at least one register memory,

said method further comprising the step of processing control information of a new composition and/or length in accordance with said second processor code.

37. (Unchanged) The method of claim 2, wherein a second receiver station includes a second plurality of processors, said method further comprising the steps of:

receiving said information transmission at a signal generator operatively connected to a transmitter;

generating (1) first cadence information which is effective at said receiver station to execute a predetermined instruction, and (2) at least one message element containing one or more instructions to be directed to a specific one of said second plurality of processors; and

embedding said cadence information and said at least one message element in said information transmission; and

communicating said information transmission, said cadence information and said at least one message element to said transmitter.

38. (Unchanged) The method of claim 37, wherein one of said second plurality of processors includes a plurality of register memories, said method further comprising the steps of:

communicating to said signal generator second cadence information which operates at said plurality of register memories to select a portion of one message of said message stream.

39. (Unchanged) The method of claim 37, wherein said signal generator embeds said generated message stream in said information transmission, said method

further comprising the step of communicating said television programming to said transmitter in said information transmission.

40. (Unchanged) The method of claim 37, wherein said second receiver station includes one of a tuner and a portion receiver operatively connected to said second plurality of processors, said method further comprising the steps of:

transmitting an instruction which operates at said receiver station to control said one of said tuner and said portion receiver to receive a signal containing at least some of said television programming; and

transmitting said television programming.

41. (Unchanged) The method of claim 3, further comprising the steps of:
generating a first instruction specifying a control function to be executed;
generating a second instruction specifying a data structure, length, or format;
organizing said first and second instructions in a sequence, said sequence comprising a command; and

communicating to a signal generator cadence information which operates at said receiver station to select a portion of one message of said message stream.

42. (Unchanged) The method of claim 41, further comprising the steps of:
processing data specifying a condition which must exist at said receiver station;
and

including said data specifying a condition in said command.

43. (Unchanged) The method of claim 41, wherein said command operates at said receiver station to execute one or more instructions contained in an instruction set,

said method further comprising the step of organizing said message stream to include said instruction set.

44. (Unchanged) The method of claim 41, further comprising the step of transmitting operating instructions which enable said receiver station to execute said control function in response to said command.

45. (Unchanged) The method of claim 41, wherein said command operates at said receiver station to present one or more receiver specific data at an output device, said receiver specific data generated in accordance with said instruction set, said method further comprising the step of transmitting one or more of (1) subscriber transaction data to be stored and processed at said receiver station and (2) meter-monitor data.

46. (Unchanged) The method of claim 41, further comprising the step of transmitting a signal which operates at said receiver station to communicate a processor interrupt to at least a portion of said plurality of processors.

47. (Unchanged) The method of claim 46, further comprising the step of transmitting an instruction which operates at said receiver station to control one of said plurality of processor to select a second processor to be interrupted.

48. (Unchanged) The method of claim 3, further comprising the steps of:
selecting at least some of said television programming at said transmission station;
selecting meter-monitor data; and

organizing said message stream to include said selected at least some of said television programming and said selected meter-monitor data.

49. (Unchanged) The method of claim 4, wherein said at least a first message contains first cadence information, a first execution segment, and an information segment, said information segment containing a first part of data and an instruction set, said method further comprising the steps of:

generating one or more second messages, each of said second messages containing second cadence information and some other part of said data and an instruction set;

organizing said first and second messages in a sequence, said sequence comprising a message stream; and transmitting said message stream.

50. (Unchanged) A method of claim 4, wherein said at least a first message contains multiple elements of fixed length, said first message including an information segment containing an instruction set, said method further comprising the steps of:

generating a second message containing multiple elements of fixed length, said multiple elements comprising a command;

firstly embedding said first message into an information transmission;

subsequently embedding said second message into said information transmission, said first message firstly and said second message subsequently in said information transmission comprising A message stream; and

transmitting said information transmission.

51. (Unchanged) The method of claim 4. wherein at least one receiver station includes a plurality of processors, said method further comprising the steps of:

selecting code to be directed to said plurality of processors;
generating one or more first elements or fields to identify a structure of said at least a first message;
generating one or more second elements or fields to identify one or more processor instructions in said at least a first message;
generating one or more third elements or fields to identify a data format in said at least a first message; and
organizing said selected code in a sequence with a plurality of message components, said sequence including said generated first, second, and third elements or fields, said selected code organized in said sequence with said plurality of message components and said generated first, second, and third elements or fields comprising said at least a first message.

52. (Unchanged) The method of claim 4, further comprising the steps of:
generating a first instruction specifying a control function to be executed;
generating a second instruction specifying a data structure, length, or format;
processing data specifying a condition, said data in said structure, length, or format specified by said second instruction;
organizing said first and second instructions and said processed data in a sequence, said sequence comprising a command;
transmitting said at least a first message and said command.

53. (Unchanged) The method of claim 4, further comprising the steps of:
receiving said information transmission at a signal generator operatively connected to said transmitter;
generating one or more second messages, said one or more second messages

containing multiple elements of fixed and variable length, said one or more second messages including (1) cadence information which is effective at one or more receiver stations to execute a predetermined instruction and (2) at least one variable length element containing one or more instructions to be directed to a processor;

embedding said second message into said first information transmission in a sequence with said first message, said first message and said second message in said first information transmission in said sequence comprising a message stream; and
transmitting said information transmission and said message stream.

54. (Unchanged) The method of claim 53, further comprising the step of transmitting at least some of said television programming.

55. (Unchanged) The method of claim 4, wherein at least one receiver station includes a plurality of processors, said method further comprising the steps of:

generating at least one fixed length message element containing specific cadence information which operates at said at least one receiver station to execute one or more preprogrammed operating instructions;

generating a plurality of variable length message elements, each variable length element containing at least one instruction and having one of (1) an internal length token, and (2) an associated signal designating a file, said plurality of variable length message elements containing instructions directed to different ones of said plurality of processors;

organizing said generated at least one fixed length message element and said generated plurality of variable length message elements in a sequence, said at least one fixed length message element and said generated plurality of variable length message elements in said sequence comprising at least a portion of a message stream; and

transmitting said message stream.

Please add the following new claims.

56. (New Claim) A method of processing signals in a television receiver, said television receiver having a plurality of processors, said method comprising the steps of:

receiving an information transmission containing digital television signals and a message stream;

detecting said message stream in said information transmission;

inputting at least a first portion of said message stream to a control processor;

selecting control information in said at least a first portion of said message stream and communicating said selected control information to at least one register memory;

comparing stored function invoking data to the contents of said at least one register memory;

inputting said digital television signals to said plurality of processors on the basis of one or more matches;

processing of said digital television signals simultaneously at two or more of said plurality of processors; and

displaying television programming contained in said digital television signals.

57. (New Claim) A method of television or video signal processing at a television or video receiver, said television or video receiver having a plurality of processors, comprising the steps of:

(1) receiving an information transmission, said information transmission containing a message stream;

54B
6167

(2) receiving a control signal which operates at a transmitter station to communicate said information transmission to a transmitter; and

(3) transmitting said message stream, said message stream enabling said receiver station to select control information in said message stream, compare said control information to a stored function invoking datum, and display television programming or video information contained in selected digital television or digital video signals on the basis of said comparison of said control information to said stored function invoking datum.

91
CM4

58. (New Claim) A method of television or video signal processing at a television or video receiver, said television or video receiver having a plurality of processors, comprising the steps of:

(1) receiving an information transmission containing a message stream; and
(2) causing said message stream to be communicated to a transmitter at a specific time, thereby to transmit said message stream, said message stream enabling said receiver station to select control information in said message stream, compare said control information to a stored function invoking datum, and display television programming or video information contained in selected digital television or digital video signals on the basis of said comparison of said control information to said stored function invoking datum.

59. (New Claim) The method of claim 56, wherein said information transmission is processed using forward error correction techniques.

60. (New Claim) The method of claim 56, further comprising the step of programming said control processor to execute a controlled function in response to said message stream.

61. (New Claim) The method of claim 56, further comprising the step of programming said control processor to compare information stored at said at least one register memory to said stored function invoking data.

91
6
com 4
62. (New Claim) The method of claim 56, further comprising the step of programming said control processor to compare information stored at said at least one register memory with information that specifies a composition of said message stream.

63. (New Claim) The method of claim 56, wherein said step of selecting control information in said at least a first portion of said message stream and communicating said selected control information to at least one register memory includes: communicating said control information to a first part of said at least one register memory; and communicating said control information to a second part of said at least one register memory.

64. (New Claim) The method of claim 56, further comprising the step of controlling a digital switch on the basis of said one or more matches.

503
617
~~65. (New Claim) The method of claim 56, wherein said digital switch communicates at least some of said digital television signals to said plurality of processors, said method further comprising the step of communicating said at least some~~

sub 67
of said message stream from said at least one register memory to one of said digital switch and a second of said plurality of processors.

66. (New Claim) The method of claim 56, wherein said control processor receives said at least a first portion of said message stream from a first of said plurality of processors, said method further comprising the step of communicating at least a second portion of said message stream to a second of said plurality of processors.

67. (New Claim) A method of processing signals at a receiver station, said receiver station having a video monitor and a plurality of processors, said method comprising the steps of:
receiving an information transmission containing digital video signals and control information;
detecting said control information in said information transmission and passing said control information to a control processor;
communicating said control information selectively to at least one register memory;
comparing stored function invoking data to the contents of said at least one register memory; communicating said digital video signals to at least one of said plurality of processors on the basis of one or more matches;
processing said digital video signals simultaneously at two or more of said plurality of processors; and displaying video contained in said digital video signals.

68. (New Claim) The method of claim 67, wherein said video includes television programming.

69. (New Claim) The method of claim 67, wherein said control information is detected in a message stream, said method further comprising the step of communicating at least some of said message stream from a first of said plurality of processors.

70. (New Claim) The method of claim 67, wherein said control processor receives said control information from a first of said plurality of processors, said method further comprising the step of communicating said control information to a second of said plurality of processors.

71. (New Claim) The method of claim 70, wherein said first processor performs one of (1) converting information detected in said message stream based on protocols and (2) assembling processor code based on data detected in at least a first portion of said information transmission, said message further comprising the step of communicating machine language code to said second processor based on data detected in at least a second portion of said information transmission.

72. (New Claim) A method of processing signals in a television receiver, said television receiver having a plurality of processors, said method comprising the steps of: receiving an information transmission containing digital television signals and cadence information; detecting and passing said cadence information to a control processor; communicating said cadence information selectively to at least one register memory; comparing stored communication control information to the contents of said at least one register memory; communicating said digital television signals to said plurality of processors on the basis of one or more matches;

SUB
G47

~~processing said digital television signals simultaneously at two or more of said plurality of processors; and
displaying television programming contained in said digital television signals.~~

73. (New Claim) The method of claim 72, wherein said control processor controls a decryptor to decrypt at least some of digital television signals, said method further comprising the step of controlling a digital switch to communicate said at least some of said digital television signals to or from said decryptor in accordance with said cadence information.

74. (New Claim) The method of claim 73, wherein said cadence information is unencrypted.

75. (New Claim) The method of claim 73, wherein said cadence information is detected in a message stream, said method further comprising the steps of:

storing a decrypted portion of said at least some of said message stream at said at least one register memory; and
processing decrypted portions of said message stream simultaneously.

76. (New Claim) The method of claim 72, wherein a standard identifies a signal to be processed, said method further comprising the step of identifying a start of one or more of (1) said digital television signals and (2) said cadence information based on said standard.

77. (New Claim) The method of claim 76, further comprising the steps of:
programming said television receiver to compare the contents of a first part of said at

least one register memory to a second part of said at least one register memory; and storing said standard at said at least one register memory.

78. (New Claim) The method of claim 76, wherein said receiver identifies, based on said standard, one of a start and an end of a message.

79. (New Claim) The method of claim 72, further comprising the step of causing said control processor to process an interrupt signal based on said cadence information.

80. (New Claim) The method of claim 56, wherein said television receiver includes a video monitor and information contained in said message stream controls a first of said plurality of processors to generate video to be displayed as part of said television programming, said method further comprising the step of communicating to said first processor a first instruction which causes said first processor to communicate said video to said video monitor.

81. (New Claim) The method of claim 80, wherein said television receiver includes a speaker and information contained in said message stream controls a second of said plurality of processors to generate an audio signal containing audio to be emitted as part of said television programming, said method further comprising the step of communicating to said second processor a second instruction which causes said second processor to communicate said audio signal to said speaker.

82. (New Claim) The method of claim 80, wherein said first of said plurality of processors generates said video in accordance with information contained in said

message stream, said method further comprising the step of communicating at least some of said message stream to said plurality of processors.

83. (New Claim) The method of claim 80, wherein at least some of said digital television signals are contained in said message stream.

84. (New Claim) The method of claim 56, wherein said message stream contains first processor code which controls said plurality of processors to generate information content of a video or audio signal, said method further comprising the steps of:

inputting to said control processor second processor code detected in said message stream; and communicating said first processor code in accordance with said second processor code.

85. (New Claim) The method of claim 84, wherein said second processor code programs said control processor to select or respond to said control information.

86. (New Claim) The method of claim 57, further comprising the steps of:
receiving said information transmission at a signal generator operatively connected to said transmitter;

generating first cadence information which is effective at said receiver to execute a predetermined instruction and at least one message element containing one or more instructions to be directed to a specific one of said plurality of processors; and

embedding said cadence information and said at least one message element in said information transmission before communicating said information transmission to said transmitter.

87. (New Claim) The method of claim 86, wherein said specific processor includes at least one register memory, said method further comprising the steps of: communicating to said signal generator second cadence information which operates at said at least one register memory to select or identify said control information.

88. (New Claim) The method of claim 57, further comprising the steps of: generating a first instruction specifying a control function to be executed; generating a second instruction specifying a data structure, length, or format; organizing said first and second instructions in a sequence, said sequence comprising a command; and embedding said command in said message stream.

Q1
E
com. 4

89. (New Claim) The method of claim 88, further comprising the steps of: processing data specifying a condition which must exist at said receiver; and including said data specifying a condition in said command.

90. (New Claim) The method of claim 88, wherein said command operates at said receiver to execute one or more instructions contained in an instruction set, said method further comprising the step of transmitting said instruction set.

91. (New Claim) The method of claim 88, further comprising the step of transmitting operating instructions which enable said receiver to execute said control function in response to said command.

92. (New Claim) The method of claim 88, wherein said command operates at said receiver to display one or more receiver specific data, said method further comprising the step of transmitting one or more of (1) subscriber transaction data to be stored and processed at said receiver and (2) meter-monitor data.

93. (New Claim) The method of claim 57, further comprising the step of transmitting a signal which operates at said receiver to communicate a processor interrupt to said plurality of processors.

94. (New Claim) The method of claim 93, further comprising the step of transmitting an instruction which operates at said receiver to control a first of said plurality of processor to selected a second processor to be interrupted.

95. (New Claim) The method of claim 93, further comprising the step of transmitting an interrupt signal standard.

96. (New Claim) The method of claim 57, further comprising the steps of:
selecting television programming;
selecting meter-monitor data; and embedding said selected television programming and said selected meter-monitor data in said message stream.

97. (New Claim) The method of claim 57, wherein information contained in said message stream enables said receiver, or apparatus operatively connected to said receiver, to select said selected digital television or digital video signals, said method further comprising the step of transmitting said digital television or digital video signals.

98. (New Claim) The method of claim 58, wherein a first message contains first cadence information, a first execution segment, and a first part of data and an instruction set, said method further comprising the steps of: generating one or more second messages, each of said second messages containing second cadence information and some other part of said data and an instruction set; and embedding said first and second messages in said message stream.

99. (New Claim) A method of claim 58, wherein said at least a first message contains multiple elements of fixed length, said first message including an information segment containing an instruction set, said method further comprising the steps of:
generating a second message containing multiple elements of fixed length, said multiple elements comprising a command; and
embedding said second message in said message stream.

100. (New Claim) The method of claim 58, further comprising the steps of:
selecting code to be directed to said plurality of processors;
generating one or more first elements or fields to identify a message structure;
generating one or more second elements or fields to identify one or more processor instructions in at least a first message; generating one or more third elements or fields to identify a data format in said at least a first message; and
organizing said selected code in a sequence with a plurality of message components, said sequence including said generated first, second, and third elements or fields, said selected code organized in said sequence with said plurality of message components and said generated first, second, and third elements or fields comprising said at least a first message.

911
con't

101. (New Claim) The method of claim 58, further comprising the steps of:
generating a first instruction specifying a control function to be executed;
generating a second instruction specifying a data structure, length, or format;
processing data specifying a condition, said data in said structure, length, or
format specified by said second instruction;
organizing said first and second instructions and said processed data in a
sequence, said sequence comprising said command; transmitting said at least a first
message and said command.

102. (New Claim) The method of claim 58, wherein said information
transmission contains a first message, said method further comprising the steps of:
receiving said information transmission at a signal generator operatively
connected to said transmitter; generating one or more second messages, said one
or more second messages containing multiple
elements of both fixed and variable length, said one or more second messages including
(1) cadence information which is effective at one or more receiver stations to execute a
predetermined instruction and (2) at least one variable length element containing one or
more instructions to be directed to said plurality of processors;
embedding said second message into said information transmission in a first
sequence with said first message; and
transmitting said information transmission and said message stream.

103. (New Claim) The method claim 102, further comprising the step of
transmitting at least some of said television programming or video information.

104. (New Claim) The method of claim 58, further comprising the steps of:

generating at least one fixed length message element containing specific cadence information which operates at said at least one receiver station to execute one or more preprogrammed operating instructions;

generating a plurality of variable length message elements, each variable length element containing at least one instruction and having one of (1) an internal length token, and (2) an associated signal designating a file, said plurality of variable length message elements containing instructions directed to different ones of said plurality of processors; and

embedding said generated at least one fixed length message element and said generated plurality of variable length message elements in said message stream.

E1
E6
COM-4

105. (New Claim) The method of claim 58, wherein said television or video receiver includes a control processor and a digital switch, said method further comprising the steps of:

generating (1) cadence information which is effective at said receiver to execute a predetermined instruction and (2) at least one message element containing one or more instructions to be directed to said control processor;

generating an execution instruction which is effective at said television or video receiver communicate said portion of one message from one of said control processor and said digital switch;

organizing said cadence information, said at least one message element, and said execution instruction in a sequence; and

communicating said cadence information, said at least one message element, and said execution instruction to said transmitter in a sequence before said specific time.

SUB
G23

106. (New Claim) A method of processing signals at a receiver station, said receiver station having a plurality of processors, said method comprising the steps of:

receiving a broadcast or cablecast information transmission containing at least one of a digital video and a digital audio signal;

detecting a message stream in said broadcast or cablecast information transmission;

selecting a message communicated in said detected message stream;

inputting at least a portion of said selected message to a control processor;

communicating a predetermined datum to a flag memory;

outputting selected portions of said message to said plurality of processors;

processing said selected portions simultaneously;

selecting a processor from said plurality of processors to interrupt on the basis of control information contained in said message;

communicating a processor interrupt to said selected processor; and

controlling apparatus presenting media programming based on the content of said flag memory.

107. (New Claim) A method of processing signals at a receiver station, said receiver station having a plurality of processors, said method comprising the steps of:

(a) receiving a broadcast or cablecast information transmission at a transmission station;

(b) generating a message that is effective to enable said receiver station to select a processor from said plurality of processors to interrupt on the basis of control information contained in said message;

(c) at least one of communicating and responding to a processor interrupt on the basis of the content of a flag memory;

(d) controlling apparatus presenting media programming based on said processor interrupt; and

(e) transmitting said message.

108. (New Claim) A method of processing signals in a network, said method comprising the steps of:

- 511
E1
CON-4
- (a) receiving a broadcast or cablecast information transmission;
 - (b) receiving an instruct signal which performs at least one of:
 - (i) effecting a transmitter station to generate a first message that is effective to enable a remote receiver station to: (1) select a processor from a plurality of processors to interrupt on the basis of control information contained in said first message, (2) at least one of communicate and respond to a processor interrupt on the basis of the content of a flag memory, and (3) control apparatus presenting media programming based on said processor interrupt; and
 - (ii) effecting a receiver station to generate a second message that is effective to enable a remote receiver station to: (1) select a processor from a plurality of processors to interrupt on the basis of control information contained in said second message, (2) at least one of communicate and respond to a processor interrupt on the basis of the content of a flag memory, and (3) control apparatus presenting media programming;
 - (c) receiving a transmitter control signal which operates at said transmitter station to communicate one of said instruct signal and said first message to a transmitter; and
 - (d) transmitting said information transmission, said transmitter control signal, and said one of said instruct signal and said first message .